

**PUBLIC SEWER DISCHARGE PERMIT**

**SUBJECT**

**MEDICHEM MANUFACTURING (MALTA) LTD.  
HF 61, HAL-FAR INDUSTRIAL ESTATE,  
HAL-FAR**

**OUR REFERENCE: DMU 5574**

**YOUR REFERENCE:**

**ACTIVITY:  
MANUFACTURING OF  
PHARMACEUTICALS**

**To whom it may concern**

Applicant, **Mr. Bernardino Mangion** has submitted an application to discharge trade effluent into the Public Sewer in terms of S.L. 545.08.

This application has been accepted and the necessary permit is hereby being issued to the applicant for the discharge from the following trade effluent source/s:  
Primary Treatment of pharmaceutical waste + pH Adjustment.

**Permit is valid for one (1) year from date of issue.**

Mr. Trevor Chircop Bray  
Managing Professional – Discharge Permitting  
Discharge Permit Unit

14 January 2020

**Conditions printed overleaf**

**Water Services Corporation**  
Triq Hal Qormi, Hal Luqa, LQA 9043, Malta

(+356) 2244 5566  
customercare@wsc.com.mt

**wsc.com.mt**



ISO 14001 applies only to WSC Main Office,  
Ta' Kandja P.S. and Pembroke R.O. Plant

### Conditions for Permit

The Water Services Corporation would have no objection to this application provided that S.L. 545.08 is adhered, in particular (but without prejudice to all other sections of the regulation):

1. Applicant shall not discharge any prohibited effluent (directly or indirectly) into the public sewerage system.
2. Applicant shall not discharge (directly or indirectly) into the public sewer any effluent containing material which alone, or in combination with the contents of the sewer, is likely:
  - ❑ To damage the sewage system, including pipe work, sumps and equipment, or block, cause overflows or in any other way interfere with the free flow of the contents of the sewer.
  - ❑ To constitute a health hazard to sewer maintenance personnel by emission of flammable, explosive, toxic, irritating or asphyxiating gases or vapours. Such material includes; volatile organic compounds (including solvents) and substances rich in sulphur and sulphur containing compounds.
  - ❑ To interfere with treatment and recovery of liquid and solid waste. Such material includes: substances that create a high oxygen demand, non-biodegradable organic matter, surfactants, salts and biocides, nitrification inhibitors, heavy metals, boron and other substances which render the recovered material unfit for re-use.
  - ❑ To bring about adverse aesthetic or other objectionable effects on the marine ecosystem upon discharge into the marine environment; floating material, settleable solids which smother benthic marine life, substances which are toxic to marine life.
3. The discharge of any substance, including such substance as is listed in Schedule B to these regulations, shall be restricted according to the provisions of regulation 5. Guideline maximum discharge concentration values for selected substances are shown in Schedule C to these regulations.
4. Applicant is to indicate suitable effluent inspection and sampling points, which points must be to the satisfaction of Managing Professional – Discharge Permitting, Water Services Corporation.
5. Applicant is to record related discharge parameters and records are to be made available to the, Managing Professional – Discharge Permitting, Water Services Corporation.
6. Maximum component discharge concentrations shall not be reached by dilution of effluent by tap water, ground water, storm water or sewage.

Applicant has **one (1) year** to present sound scientific evidence, to the satisfaction of the Managing Professional – Discharge Permitting that they are adhering to S.L. 545.08.

The above-mentioned conditions are without prejudice to all other sections laid down in S.L. 545.08.

**Failure to comply with the above mentioned conditions or any other article in S.L. 545.08 shall nullify such permit.**

--