

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.0 Revision Date 06.12.2013

Print Date 28.04.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : *N,N*-Dimethylformamide

Product Number : 227056
Brand : Sigma-Aldrich
Index-No. : 616-001-00-X
REACH No. : 01-2119475605-32-XXXX
CAS-No. : 68-12-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Company Ltd.
The Old Brickyard
NEW ROAD, GILLINGHAM
Dorset
SP8 4XT
UNITED KINGDOM

Telephone : +44 (0)1747 833000
Fax : +44 (0)1747 833313
E-mail address : eurtechserv@sial.com

1.4 Emergency telephone number

Emergency Phone # : +44 (0)1747 833100

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226
Acute toxicity, Inhalation (Category 4), H332
Acute toxicity, Dermal (Category 4), H312
Eye irritation (Category 2), H319
Reproductive toxicity (Category 1B), H360D

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Xn	Harmful	R61
Xi	Irritant	R20/21
		R36

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word : Danger

Hazard statement(s)
H226 Flammable liquid and vapour.
H312 + H332 Harmful in contact with skin or if inhaled
H319 Causes serious eye irritation.
H360D May damage the unborn child.

Precautionary statement(s)
P201 Obtain special instructions before use.
P280 Wear protective gloves/ protective clothing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard Statements none

Restricted to professional users.

2.3 Other hazards

Rapidly absorbed through skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : DMF

Formula : C₃H₇NO

Molecular Weight : 73.09 g/mol

CAS-No. : 68-12-2

EC-No. : 200-679-5

Index-No. : 616-001-00-X

Registration number : 01-2119475605-32-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
N,N-Dimethylformamide Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)		
CAS-No. 68-12-2	Flam. Liq. 3; Acute Tox. 4; Eye Irrit. 2; Repr. 1B; H226, H319, H312, H332, H360D	<= 100 %
EC-No. 200-679-5		
Index-No. 616-001-00-X		
Registration number 01-2119475605-32-XXXX		

Hazardous ingredients according to Directive 1999/45/EC

Component	Classification	Concentration
N,N-Dimethylformamide Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)		
CAS-No. 68-12-2	T, Repr.Cat.2, R61 - R20/21 - R36	<= 100 %
EC-No. 200-679-5		
Index-No. 616-001-00-X		
Registration number 01-2119475605-32-XXXX		

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides, nitrogen oxides (NO_x)

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
N,N-Dimethylformamide	68-12-2	STEL	10 ppm 30 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
	Remarks	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	5 ppm 15 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
		Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	5 ppm 15 mg/m3	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
		Identifies the possibility of significant uptake through the skin Indicative		
		STEL	10 ppm 30 mg/m3	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
		Identifies the possibility of significant uptake through the skin Indicative		

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Skin contact	Acute systemic effects	26.3mg/kg BW/d
Workers	Inhalation	Acute systemic effects	30 mg/m3
Workers	Skin contact	Long-term systemic effects	3.31mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	15 mg/m3
Workers	Inhalation	Long-term local effects	15 mg/m3
Workers	Inhalation	Acute local effects	30 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Water	30 mg/l
Soil	16.235 mg/kg
Marine water	3 mg/kg
Fresh water	30 mg/l
Fresh water sediment	25.05 mg/kg
Onsite sewage treatment plant	123 mg/l

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 30 min

Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--------------------|---|
| a) Appearance | Form: liquid, clear
Colour: colourless |
| b) Odour | amine-like |
| c) Odour Threshold | no data available |
| d) pH | 6.7 |

e) Melting point/freezing point	Melting point/range: -61 °C
f) Initial boiling point and boiling range	153 °C
g) Flash point	58 °C - closed cup
h) Evaporation rate	no data available
i) Flammability (solid, gas)	no data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 15.2 %(V) Lower explosion limit: 2.2 %(V)
k) Vapour pressure	3.60 hPa at 20 °C 5.16 hPa at 25 °C
l) Vapour density	2.52 - (Air = 1.0)
m) Relative density	0.944 g/mL
n) Water solubility	completely miscible
o) Partition coefficient: n-octanol/water	log Pow: -1.01
p) Auto-ignition temperature	no data available
q) Decomposition temperature	no data available
r) Viscosity	no data available
s) Explosive properties	no data available
t) Oxidizing properties	no data available

9.2 Other safety information

Relative vapour density 2.52 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Other decomposition products - no data available
In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - rat - 2,800 mg/kg

LC50 Inhalation - rat - 4 h - 9 - 15 mg/l

LD50 Dermal - rabbit - 1,500 mg/kg

Skin corrosion/irritation

Skin - Human

Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation

Eyes - rabbit

Result: Moderate eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

mouse

lymphocyte

Mutation in mammalian somatic cells.

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (N,N-Dimethylformamide)

Reproductive toxicity

May cause congenital malformation in the fetus.

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

RTECS: LQ2100000

Warning: intolerance for alcohol can occur up to 4 days after dimethylformamide exposure. N,N-dimethylformamide is considered to be a potent liver toxin., Vomiting, Diarrhoea, Abdominal pain, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 9,000 - 13,000 mg/l - 96 h
	LC50 - Lepomis macrochirus (Bluegill) - 6,700 - 7,500 mg/l - 96 h
	LC50 - Pimephales promelas (fathead minnow) - 10,400 - 10,800 mg/l - 96 h
	LC50 - Oncorhynchus mykiss (rainbow trout) - 9,800 mg/l - 96 h
	LC50 - Lepomis macrochirus (Bluegill) - 6,300 mg/l - 96 h
	LC50 - Pimephales promelas (fathead minnow) - 10,600 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 9,600 - 13,100 mg/l - 48 h
	EC50 - Daphnia magna (Water flea) - 15,700 mg/l - 48 h
Toxicity to algae	LC50 - Desmodesmus subspicatus (green algae) - > 500 mg/l - 96 h

12.2 Persistence and degradability

Biodegradability Result: > 90 % - Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: 2265

IMDG: 2265

IATA: 2265

14.2 UN proper shipping name

ADR/RID: N,N-DIMETHYLFORMAMIDE

IMDG: N,N-DIMETHYLFORMAMIDE

IATA: N,N-Dimethylformamide

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

no data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Authorisations and/or restrictions on use**

N,N-Dimethylformamide

CAS-No.: 68-12-2

Candidate List of Substances of Very High Concern for Authorisation

Toxic for reproduction (article 57c)

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3.**

Acute Tox.	Acute toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H360D	May damage the unborn child.
Repr.	Reproductive toxicity

Full text of R-phrases referred to under sections 2 and 3

T	Toxic
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R61	May cause harm to the unborn child.
Repr.Cat.2	Toxic to Reproduction Category 2

Further information

Copyright 2013 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Annex: Exposure scenario

Identified uses:

Use: Used as chemical intermediate

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC19: Intermediate
PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

Use: Formulation of preparations

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
ERC2: Formulation of preparations

Use: Industrial use of processing aids in processes and products, not becoming part of articles

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Use: Used as laboratory reagent.

SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 3, SU 22, SU24: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen), Scientific research and development
PC21: Laboratory chemicals
PROC15: Use as laboratory reagent
ERC4, ERC6a: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates)

1. Short title of Exposure Scenario: Used as chemical intermediate

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC19

Process categories : PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9
Environmental Release Categories : ERC6a:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PC19

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Low volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.0355 mg/m3	0.002
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0172 mg/kg BW/d	0.005
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.3546 mg/m3	0.024
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.021
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.0639 mg/m3	0.071
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0172 mg/kg BW/d	0.005

PROC4	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.5319 mg/m3	0.035
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : SU 3
Sectors of end-use : SU 10
Process categories : PROC5, PROC8b, PROC9
Environmental Release Categories : ERC2:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC5, PROC8b, PROC9

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Low volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.6857 mg/kg BW/d	0.207
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.5319 mg/m3	0.035
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups : **SU 3**
 Sectors of end-use : **SU 3, SU9**
 Process categories : **PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9**
 Environmental Release Categories : **ERC4:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9

Product characteristics

Concentration of the Substance in : Covers the percentage of the substance in the product up to

Mixture/Article 100 % (unless stated differently).
Physical Form (at time of use) : Low volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0172 mg/kg BW/d	0.005
PROC1	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.0355 mg/m3	0.002
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0.021
PROC2	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.3546 mg/m3	0.024
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0172 mg/kg BW/d	0.005
PROC3	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.0639 mg/m3	0.071
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118
PROC4	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.3429 mg/kg BW/d	0.104
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	0.5319 mg/m3	0.035
PROC9	ECETOC TRA	With Local	Dermal	0.3429 mg/kg	0.104

		Exhaust Ventilation		BW/d	
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent.

Main User Groups : SU 22
Sectors of end-use : SU 3, SU 22, SU24
Chemical product category : PC21
Process categories : PROC15
Environmental Release Categories : ERC4, ERC6a:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC15, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Low volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment	Specific conditions	Value	Level of Exposure	RCR*
-----------------------	---------------------	---------------------	-------	-------------------	------

	Method				
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	1.7731 mg/m3	0.118
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0171 mg/kg BW/d	0.005

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).
