

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.1 Revision Date 12.10.2013

Print Date 18.04.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Sulfuric acid

Product Number : 435589

Brand : Sigma-Aldrich

Index-No. : 016-020-00-8

REACH No. : 01-2119458838-20-XXXX

CAS-No. : 7664-93-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Company Ltd.
The Old Brickyard
NEW ROAD, GILLINGHAM
Dorset
SP8 4XT
UNITED KINGDOM

Telephone : +44 (0)1747 833000

Fax : +44 (0)1747 833313

E-mail address : eurtechserv@sial.com

1.4 Emergency telephone number

Emergency Phone # : +44 (0)1747 833100

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Skin corrosion (Category 1A), H314

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

C Corrosive R35

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements**Labelling according Regulation (EC) No 1272/2008**

Pictogram



Signal word : Danger

Hazard statement(s)
H314

Causes severe skin burns and eye damage.

Precautionary statement(s)
P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove

P310 contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/ physician.

Supplemental Hazard Statements none

2.3 Other hazards - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : sulfuric acid (Solution)

Formula : $\text{H}_2\text{O}_4\text{S}$

Molecular Weight : 98.08 g/mol

CAS-No. : 7664-93-9

EC-No. : 231-639-5

Index-No. : 016-020-00-8

Registration number : 01-2119458838-20-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

| Component | Classification | Concentration |
|---|---------------------|---------------|
| Sulfuric acid | | |
| CAS-No. 7664-93-9 | Skin Corr. 1A; H314 | 50 - 100 % |
| EC-No. 231-639-5 | | |
| Index-No. 016-020-00-8 | | |
| Registration number 01-2119458838-20-XXXX | | |

Hazardous ingredients according to Directive 1999/45/EC

| Component | Classification | Concentration |
|---|----------------|---------------|
| Sulfuric acid | | |
| CAS-No. 7664-93-9 | C, R35 | 50 - 100 % |
| EC-No. 231-639-5 | | |
| Index-No. 016-020-00-8 | | |
| Registration number 01-2119458838-20-XXXX | | |

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Sulphur oxides, Hydrogen sulfide gas

Sulphur oxides

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

no data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

A part from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|---------------|-----------|---|------------------------|--|
| Sulfuric acid | 7664-93-9 | TWA | 0.05 mg/m ³ | Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC |
| | Remarks | When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. Indicative | | |

| | | | | |
|--|--|---|------------------------|--|
| | | TWA | 0.05 mg/m ³ | UK. EH40 WEL - Workplace Exposure Limits |
| | | Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used | | |

Derived No Effect Level (DNEL)

| Application Area | Exposure routes | Health effect | Value |
|------------------|-----------------|-------------------------|------------------------|
| Workers | Inhalation | Acute local effects | 0.1 mg/m ³ |
| Workers | Inhalation | Long-term local effects | 0.05 mg/m ³ |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|-------------------------------|--------------|
| Marine water | 0.00025 mg/l |
| Fresh water | 0.0025 mg/l |
| Marine sediment | 0.002 mg/kg |
| Fresh water sediment | 0.002 mg/kg |
| Onsite sewage treatment plant | 8.8 mg/l |

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

| | |
|---|---------------------------------|
| a) Appearance | Form: clear, liquid |
| b) Odour | no data available |
| c) Odour Threshold | no data available |
| d) pH | 1.2 at 5 g/l |
| e) Melting point/freezing point | 3 °C |
| f) Initial boiling point and boiling range | 290 °C - lit. |
| g) Flash point | not applicable |
| h) Evaporation rate | no data available |
| i) Flammability (solid, gas) | no data available |
| j) Upper/lower flammability or explosive limits | no data available |
| k) Vapour pressure | 1.333 hPa at 145.8 °C |
| l) Vapour density | no data available |
| m) Relative density | 1.84 g/cm ³ at 25 °C |
| n) Water solubility | soluble |
| o) Partition coefficient: n-octanol/water | no data available |
| p) Auto-ignition temperature | no data available |
| q) Decomposition temperature | no data available |
| r) Viscosity | no data available |
| s) Explosive properties | no data available |
| t) Oxidizing properties | no data available |

9.2 Other safety information

| | |
|-----------------|--------------------|
| Surface tension | 55.1 mN/m at 20 °C |
|-----------------|--------------------|

SECTION 10: Stability and reactivity**10.1 Reactivity**

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

Avoid moisture.

10.5 Incompatible materials

Bases, Halides, Organic materials, Carbides, Chlorates, fulminates, Nitrates, picrates, Cyanides, Reacts violently with: cyclopentadiene, cyclopentanone oxime, nitroaryl amines, hexalithium disilicide, phosphorous(III) oxide, Powdered metals

10.6 Hazardous decomposition products

Other decomposition products - no data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - rat - 2,140 mg/kg (Sulfuric acid)

LC50 Inhalation - rat - 2 h - 510 mg/m³ (Sulfuric acid)

Skin corrosion/irritation

Skin - rabbit

Result: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Eyes - rabbit (Sulfuric acid)

Result: Severe eye irritation

Respiratory or skin sensitisation

no data available (Sulfuric acid)

Germ cell mutagenicity

no data available (Sulfuric acid)

Carcinogenicity

The International Agency for Research on Cancer (IARC) has determined that occupational exposure to strong-inorganic-acid mists containing sulfuric acid is carcinogenic to humans (group 1). (Sulfuric acid)

IARC: 1 - Group 1: Carcinogenic to humans (Sulfuric acid)

Reproductive toxicity

no data available (Sulfuric acid)

Specific target organ toxicity - single exposure

no data available (Sulfuric acid)

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available (Sulfuric acid)

Additional Information

RTECS: Not available

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Pulmonary edema. Effects may be delayed., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. (Sulfuric acid)

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Gambusia affinis (Mosquito fish) - 42 mg/l - 96 h (Sulfuric acid)

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available (Sulfuric acid)

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1830

IMDG: 1830

IATA: 1830

14.2 UN proper shipping name

ADR/RID: SULPHURIC ACID

IMDG: SULPHURIC ACID

IATA: Sulphuric acid

14.3 Transport hazard class(es)

ADR/RID: 8

IMDG: 8

IATA: 8

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

no data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

no data available

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H314

Causes severe skin burns and eye damage.

Skin Corr.

Skin corrosion

Full text of R-phrases referred to under sections 2 and 3

C Corrosive
R35 Causes severe burns.

Further information

Copyright 2013 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Annex: Exposure scenario

Identified uses:

Use: Used as chemical intermediate

| |
|--|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals |
| PROC1: Use in closed process, no likelihood of exposure |
| PROC2: Use in closed, continuous process with occasional controlled exposure |
| PROC3: Use in closed batch process (synthesis or formulation) |
| PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises |
| PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities |
| PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) |
| PROC15: Use as laboratory reagent |
| ERC1: Manufacture of substances |

Use: Formulation of preparations

| |
|---|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys) |
| PROC1: Use in closed process, no likelihood of exposure |
| PROC3: Use in closed batch process (synthesis or formulation) |
| PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) |
| PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities |
| PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) |
| ERC2: Formulation of preparations |

Use: Used as laboratory reagent.

| |
|---|
| SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| SU 3, SU 22, SU24: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen), Scientific research and development |
| PC21: Laboratory chemicals |
| PROC15: Use as laboratory reagent |
| ERC4, ERC6a: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates) |

1. Short title of Exposure Scenario: Used as chemical intermediate

| | |
|----------------------------------|--|
| Main User Groups | : SU 3 |
| Sectors of end-use | : SU 3, SU9 |
| Process categories | : PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15 |
| Environmental Release Categories | : ERC1: |

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC1

Product characteristics

| | |
|---|--|
| Concentration of the Substance in Mixture/Article | : Covers the percentage of the substance in the product up to 100 % (unless stated differently). |
|---|--|

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|--------------------------------|------------|-------------------|-------|
| PROC1 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0 mg/m3 | 0 |
| PROC2 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0 mg/m3 | 0 |
| PROC3 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.0004 mg/m3 | 0.008 |
| PROC4 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.014 mg/m3 | 0.28 |
| PROC8b | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0 mg/m3 | 0 |
| PROC9 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.003 mg/m3 | 0.06 |
| PROC15 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.0002 mg/m3 | 0.004 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : SU 3
Sectors of end-use : SU 10
Process categories : PROC1, PROC3, PROC5, PROC8b, PROC9
Environmental Release Categories : ERC2:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC5, PROC8b, PROC9

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|--------------------------------|------------|-------------------|-------|
| PROC1 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0 mg/m3 | 0 |
| PROC3 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.0004 mg/m3 | 0.008 |
| PROC5 | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0.018 mg/m3 | 0.36 |
| PROC8b | ECETOC TRA | With Local Exhaust Ventilation | Inhalation | 0 mg/m3 | 0 |
| PROC9 | ECETOC TRA | With Local | Inhalation | 0.003 mg/m3 | 0.06 |

| | | | | | |
|--|--|------------------------|--|--|--|
| | | Exhaust Ventilation | | | |
|--|--|------------------------|--|--|--|

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent.

Main User Groups : SU 22
 Sectors of end-use : SU 3, SU 22, SU24
 Chemical product category : PC21
 Process categories : PROC15
 Environmental Release Categories : ERC4, ERC6a:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC15, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|---------------------|------------|-------------------|-------|
| PROC15 | ECETOC TRA | With Local Exhaust | Inhalation | 0.0002 mg/m3 | 0.004 |

| | | | | | |
|--|--|-------------|--|--|--|
| | | Ventilation | | | |
|--|--|-------------|--|--|--|

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).
